## **AMMA** 7236

72" x 36" x 21"

Amma takes its origin in the word "massage" as represented by two Chinese characters, AN and MO, meaning "calm through touch."

## PRODUCT NO.

DESCRIPTION	тми	TUB	
	BAMSRB00T-XX	BAMSRB00N-XX	

THERMOMASSEUR (TMU) Hydro-thermo massage • Air jet system	\$
Jets	54
2 heated backrests & headrests*	Included
MiaPlus® Control	Included
Geysair®	Included
AromaCloud®** BAROMAC	\$
Illuzio Chromatherapy BCHRO6	\$

<b>TUB</b> Soaker	\$
AromaCloud®** BAROMAC	\$
Illuzio Chromatherapy BCHRO6	\$
WarmTouchShell® BWTS	\$
DOT control	Included with therapy
2 <sup>nd</sup> WarmTouchShell® BWTS2	\$

FEATURES				
Installation type		Drop-in & Alcove (3 walls)		
No. of bathers	* *	Inverted V		2
US gallons	50	Armrests		4
Imp. gallons	41	Grab bars (color match)		2
Raised seats	2			
STANDARD COLOR				
White 01 Biscuit 02				Included

		OPTIONS (UPCHARGE APPLICABLE)			
COLOR					
Gray 05		\$			
CONTROL (TMU only)					
MiaMulti® BMIAM2-XX		\$			
SKIRT	MULTIFIT BSMUL-XX	SJ-1 BSJ1-XX			
White 01, Biscuit 02	\$	\$			
Gray 05	\$	\$			
CLEAR ACRYLIC GRAB BARS BGBG10-XX					
With Chrome 07 or Brushed Nickel 09 inserts		\$			
WASTE & OVERFLOW	<b>16" x 35"</b> BOVER16-XX	INTE- GRATED BOVERIN-XX			
Chrome 07	\$	\$			
White 01, Biscuit 02	\$	\$			
White 01, Biscuit 02 Brushed Nickel 09, Polished Nickel 10	\$	\$			
·		\$			
Brushed Nickel 09, Polished Nickel 10	\$	\$			
Brushed Nickel 09, Polished Nickel 10 Oil-rubbed Bronze 11	\$	\$ N/A			
Brushed Nickel 09, Polished Nickel 10 Oil-rubbed Bronze 11 Black Chrome 12, Matte Black 19, Satin Brass 18	\$	\$ N/A			
Brushed Nickel 09, Polished Nickel 10 Oil-rubbed Bronze 11 Black Chrome 12, Matte Black 19, Satin Brass 18 TILE FLANGE (specify front or back)	\$	\$ N/A			
Brushed Nickel 09, Polished Nickel 10 Oil-rubbed Bronze 11 Black Chrome 12, Matte Black 19, Satin Brass 18 TILE FLANGE (specify front or back) Ordered with bath (not installed) BTILEN Factory-installed, Front BTILEF, Back BTILEB,	\$ \$ N/A	\$ N/A \$ \$			
Brushed Nickel 09, Polished Nickel 10 Oil-rubbed Bronze 11 Black Chrome 12, Matte Black 19, Satin Brass 18 TILE FLANGE (specify front or back) Ordered with bath (not installed) BTILEN Factory-installed. Front BTILEF, Back BTILEB, Special installation BTILEO	\$ \$ N/A	\$ N/A \$ \$			
Brushed Nickel 09, Polished Nickel 10 Oil-rubbed Bronze 11 Black Chrome 12, Matte Black 19, Satin Brass 18 TILE FLANGE (specify front or back) Ordered with bath (not installed) BTILEN Factory-installed. Front BTILEF, Back BTILEB, Special installation BTILEO  IF REQUIRED BY CONSTRUCTION CODE OR	\$ \$ N/A	\$ N/A \$ \$ \$ \$ \$ WITH ITD			



- \* Independently controlled.

  \*\* The AromaCloud® is built into the deck.

  \*\*\* When ordered with integrated waste & overflow.









## **AMMA** 7236

## INSTALLATION

(A) When tile flange is added, the AromaCloud® will automatically be installed on the opposite side of the flange.





LETTER	DESCRIPTION	MEASURE
Α	Outside edge to center drain	12"
В	Outside edge to overflow	4 1/4"
С	Total length	72"
D	Total width	36"
E	Bathing well length	52 1/2"
F	Bathing well width at foot area	18 3/4"
G	Raised seat length	18 1/2"
Н	Raised seat width	21 3/4"
ı	Deck width (narrowest point)	3 1/8"
J	Deck width (widest point)	4"
K	Deck width at backrest end end	2"
L	Total height to headrest	23 1/8"
М	Height from bottom of tub to top deck	21"
N	Height from bottom of tub to bottom of lip	19 1/2"
0	Height from drain to center of overflow	17"
P	Maximum water level	15 1/4"
Q	Slope of backrest	17°

- ⚠ AromaCloud® position
- Control position when factory-installed (Mia® or DOT)
- Turbine position (TMU)
- Indicates heated backrest (TMU)
- Indicates WarmTouchShell® position (TUB)

TECHNICAL SP	ECIFICATIONS		
Hot water	Should be 70% of water capacity of TUB or greater.	Approx. shipping weight	158 lbs
supply required	·	Turbine power	550 W
Touching	Access to the pump must be at least 18" x 22". <b>Standard connection is 20 A. 120 V, 60 hz</b> , dedicated line with a Ground-Fault Circuit Interrupter (GFCI). <b>For any additional option</b> ,	Air heater	600 W
	a second line is needed 15 A. 120 V, 60 hz, dedicated line with a GFCI. Air vent necessary: 2" x 4" minimum.	WARRANTY	
Other	Optional tile flange (specify front or back).	Controls-LED-Geysair*	5 years
Our products must be installed by certified professionals only and according to our Owner's Manual as well as federal, provincial/state and local building codes and regulations (www.bainultra.com/documentation/documentation).		Bath & turbine*	20 years
		* Some restrictions apply   www.bainultra.com/warranty	





The specifications shown indicate the outer edge dimension and the inside bathing capacity dimension measured at air jets' height. The manufacturer accepts a 1/4" [0.64 cm] variance. There are variations on each product and specifications are subject to change as we improve upon our product as required. The dimensions needed for site preparation and structure building will differ. BainUltra® assumes no responsibility for preparatory work done prior to the product being on site.