



RECTANGULAR SHOWERS



Shower Size	A	В	С	D	E	F
32" x 48"	48"	32"	33½"	24"	16"	331/4"
34" x 48"	48"	34	35½"	24"	17"	35¼"

Shower shown with optional StyleMate® By-Pass Door. See available models below.





See page 5 for valve placement.

Specifications



32"x 48" Showers

DURAWALL® SHOWER WALLS

748-32WHT 748-32BN White Bone



34"x 48" Showers

Model Color/Glass

DURAWALL® SHOWER WALLS

748-34WHT 748-34BN White Bone





DURABASE® SHOWER FLOOR

3248M	
3248BN	





DURABASE® SHOWER FLOOR

3448M	Whi
3448BN	Bon





STYLEMATE® BY-PASS ENCLOSURE — Height 69"

Bone

rramea aesign			
48.403	Chrome/Clear		
48.404	Brushed Nickel/Clear		
48.405	Oil-Rubbed Bronze/Clear		
Frameless design			
48.406	Chrome/Clear		
48.407	Brushed Nickel/Clear		
48 408	Oil-Rubbed Bronze/Clear		

STYLEMATE® BY-PASS ENCLOSURE — Height 69"

Framed design 48.403

48.404	Brushed Nickel/Clear		
48.405	Oil-Rubbed Bronze/Clear		
Frameless design			
48.406	Chrome/Clear		
48.407	Brushed Nickel/Clear		
18 108	Oil-Rubbed Bronze /Clear		

Chrome/Clear

General: Furnish and install as shown on plans, a Shower Ensemble, as manufactured by E. L. Mustee & Sons, Inc., consisting of:

DURAWALL* Shower Walls — Model: ______ (748-32 or 748-34) shall be semi-gloss, 3-piece wall. Panels are molded fiberglass, using matched metal molds under extreme heat and pressure with a minimum uniform thickness of 125 mils and mount direct-to-studwalls. Include center panel with molded-in shelf and two side panels, each with molded-in shelf. Self-aligning panels using a tongue-and-groove connection. Shall meet ANSI Specification Z 124.1.2. Color: ______ (White, Bone).

DURABASE® Shower Floors — Model: ______ refer to page 12 & 13 for specifications. STYLEMATE® By-Pass Enclosures — Model: ______ refer to page 11 for specifications.